



TangoRail®



TR100, TR150, TR200 & TR250 Tubular Fencing General Specifications

Tube Material	25.4mm x 2mm Tubes spaced at 100 mm (TR100 & TR200) or 75mm (TR150 & TR250) Galvanised and Powdercoated to AS1627, part 6/1977. Total minimum zinc coating of 100g/m ²
HD Rail	Roll formed 55mm x 50 mm x 2.0 mm Galvanised and Powdercoated to AS1627, part 6/1977
LD Rail	Roll formed 55mm x 25 mm x 2.0 mm Galvanised and Powdercoated to AS1627, part 6/1977
TFB Post	100mm x 45mm 7.2 kg /m Galvanised and Powdercoated to AS1627, part 6/1977
Post Fixings (TFB Post)	Flat Bar (Fishplate) 95 mm x 25 mm x 6 mm Connected using 4 of 10 x 50 galvanised bolts and anti-tamper snap off nuts.
Round Post	60.3mm x 2.5mm Galvanised and Powdercoated to AS1627, part 6/1977
Post Fixings (Round Post)	Formed bracket 60 mm x 60 mm x 130 mm x 2.5 mm (TangoLok) Connected using 2 anti removal sleeves and 2 70mm x 10mm galvanised bolts and anti-tamper snap off nuts. Galvanised and Powdercoated to AS1627, part 6/1977
Midbay Supports	250mm x 32mm x 2.5mm tube with securing bolt. Galvanised and Powdercoated to AS1627, part 6/1977



TangoRail®



TR100, TR150, TR200 & TR250

Tubular Fencing General Specifications Continued ...

Component Lists by Height

TR100 / TR200	1.5m high	1.8m high
Bay Width	2.75m	2.75m
Post	1 Round Post	1 Round Post
Tube	21 tubes	21 tubes
Rail (recommended)	2 LD Rails	2 LD Rails
Fixings	4 TangoLoks 4 sleeves 4 nuts and bolts	4 Tangoloks 4 sleeves 4 nuts and bolts
Midbay	1 support tube	1 support tube
Weight per metre	23 kgs/m	29 kgs/m

TR100 / TR200	2.1m high	2.4m high
Bay Width	2.75m	2.75m
Post	1 Round Post	1 Rolled Post
Tube	21 tubes	21 tubes
Rail (recommended)	3 LD Rails	3 HD Rails
Fixings	6 Tangoloks 6 sleeves 6 nuts and bolts	2 Fishplates 4 nuts and bolts
Midbay	1 support tube	1 support tube
Weight per metre	35 kgs/m	38 kgs/m

TR150 / TR250	1.8m high	2.1m high	2.4m high
Bay Width	2.75m	2.75m	2.75m
Post	1 Rolled Post	1 Rolled Post	1 Rolled Post
Tube	26 tubes	26 tubes	26 tubes
Rail (recommended)	2 HD Rails	3 HD Rails	3 HD Rails
Fixings	2 Fishplates 4 nuts and bolts	3 Fishplates 6 nuts and bolts	3 Fishplates 6 nuts and bolts
Midbay	1 support tube	1 support tube	1 support tube
Weight per metre	32 kgs/m	38 kgs/m	40 kgs/m