



GRYFFIN Pty. Ltd.

ABN 16 125 989 683

PO Box 665 Bayswater

Victoria, 3153 Australia

Telephone : 61 (03) 9761 4522

Fax : 61 (03) 9761 4134

Email : sales@gryffin.com.au

Website : <http://www.gryffin.com.au>

TIGERTAPE™ Long Barbed Tape

Core Reinforced - Stainless Steel Concertina

General Specifications

STAINLESS STEEL TAPE

301 grade Austenitic. 0.5mm thick(± 0.06).
3/4 hard to HV370 ± 20 (min).
T.S 1158 Mpa(min). YP 866 Mpa(min).
Australian standard AS 1449 301

TAPE CONFIGURATION

Clusters of four barbs at 100mm centres.
Each barb 30mm (approx) long with needle sharp points.

CONCERTINA FORMAT

Alternate pairs of adjacent loops joined at regular intervals around circumference.
630mm \varnothing = 3 clips
760mm \varnothing = 3 (or 5) clips
900mm \varnothing = 5 clips
1300mm \varnothing = 7 clips
1500mm \varnothing = 9 clips

FIXING TIES

1.2mm \varnothing Stainless steel twist ties.

CORE WIRE (GALVANISED)

2.5mm \varnothing drawn heavy galvanised spring steel quality.
Zinc Coating 16(± 1 gm/cm²).
T.S. 1730 Mpa($\pm 5\%$) (Kg force 170 Kg/cm²($\pm 5\%$))
Australian standard AS 1472/1979

CONCERTINA CLIPS

1.5mm thick x 10 mm wide 304 grade stainless steel.
Fully clenched, interlocking tongue
Origin : Australia

RECOMMENDED SPACING

One loop per 150mm max
(One clipped pair at 300mm centres).

WELDMESH SUPPORT

Galvanised weldmesh
4mm wire x 75mm horizontal x 25mm vertical.
Cropped and press formed to suit individual application.
Origin : Australia

Note : Materials can be varied according to customer's requirements & all product is manufactured at our factory in Melbourne, Victoria.