



KABA[®]

Talos revolving doors

Design and functionality

«Our entrance area is our hotel's business card – it's the first impression our guests gain on arrival and it's one that lasts. Our choice has been a Talos all-glass revolving door. Along with the stylish design we really appreciate the excellent thermal insulation it provides and how easy it is to pass through – even with luggage.»





Talos revolving doors

Talos revolving doors provide an energy efficient solution for entrance areas thanks to their thermal separation design incorporated into the façade of a building. As an option, revolving doors can be equipped with a number of features to suit our customers' demands: access for people with reduced mobility, emergency escape function, integration of manual or motor-driven night shutters and many more.

By choosing the appropriate options

Talos revolving doors can be made to meet various safety and security requirements (e.g. burglar or fire-resistant).



Swing or sliding doors installed to one side of revolving doors provide access for people with reduced mobility.

Why Talos revolving doors?



2

- excellent thermal insulation
- customised design
- solutions for emergency escape routes
- stylish all-glass versions



Fields of application

- Hotels
- Office and administrative buildings
- Shopping malls
- Airports
- Stations
- Hospitals
- Banks and financial institutions
- Museums
- Concert halls



A smart solution for any entrance



Equipped for an emergency - four-wing revolving door with approved emergency escape column



Additional security - four-wing revolving door with night shutters



All-glass design revolving door with under-floor drive

4



Revolving doors with eye-catching glossy finish



Stylish integration - All-glass revolving door in classical building



Approved emergency escape column - The door wings can be manually folded back, giving the way free in case of emergency

Talos revolving doors

Four versions, multiple options

Talos RDR-E01



Talos RDR-C01



Outside Ø in mm	2100 to 3600	2100 to 3600
Side walls	glass or metal-clad	glass or metal-clad
Number of wings	3 or 4	3 or 4
Manual	standard	standard
Automatic	optional	optional
Disabled function	standard for automatic units	standard for automatic units
Emergency escape function	-	optional
Night shutters	optional	optional
Burglar resistant	-	optional

Talos RDR-C03



Talos RDR-S01



Outside Ø in mm	2100 to 3600	2100 to 3300
Side walls	glass or metal-clad	glass
Number of wings	3 or 4	3 or 4
Manual	optional	standard
Automatic	standard	optional
Disabled function	standard	standard for automatic units
Emergency escape function	standard	-
Night shutters	optional	optional
Burglar resistant	-	optional



Kaba Australia Pty. Limited
PAS Division - Physical Access Solutions
16-18 Carlotta Street
Artarmon NSW 2064
Australia
Tel: 02 9438 5533
Fax: 02 9437 4535

www.kaba.com.au
pas@kaba.com.au