

AquaDeck

Anti-slip wet area floor covering

MATERIAL DESCRIPTION

AquaDeck anti-slip floor or deck covering is produced from a unique combination of polymers, fine cork granules and rubber to form a stable, homogenous and hard wearing anti-slip floor or deck covering which is highly suited to wet or dry conditions. The polymer compound has been formulated to give AquaDeck superior weathering characteristics under the harsh Australian climatic conditions.

The raised surface has been designed to complement the appearance of any floor or deck surface.

APPLICATIONS

AquaDeck is ideally suited for:

- Areas of excessive wet conditions.
- Marine decking.
- Pleasure craft.
- Pontoon decking.
- Swimming pool surrounds.
- House boats.
- Walkways.
- Stairways.
- Work boats.

SPECIAL FEATURES

- Cost efficient.
- Anti-slip even when wet.
- Aids safety.
- Aesthetically pleasing.
- Comfortable.
- Impact absorbing.
- High wear-resistance.
- High thermal properties.
- High chemical resistance.
- Easy to install.
- Highly flexible.
- Fire retardant.
- Available in sheet form.
- Low maintenance.

SLIP RESISTANCE

AquaDeck has a textured surface created by the inclusion of cork, a natural friction material which provides a surface finish having a very high co-efficient of friction even when wet.

WEAR RESISTANT

AquaDeck is a tough "cushion" floor covering which will resist damage under normal heavy-duty conditions.

THERMAL CHARACTERISTICS

AquaDeck is thermally stable and will not crack or craze under expansion and contraction of the substrate. AquaDeck has low thermal conductivity aiding insulation of cabin areas.

SOUND REDUCTION

AquaDeck is a highly resilient product that has the ability to absorb impact and thus reduce the transfer of sound energy (noise) to the surrounding environment.

RESISTANT PROPERTIES

AquaDeck is resistant to attack from ultra violet, oil, grease, petrol, diesel, diluted acids and chlorine, salt and moisture.

COLOURS

Teak, steel grey, green, pacific blue, sand and black.

DIMENSIONS

Sheet: 1800 x 900 x 3 mm

INSTALLATION

AquaDeck should be butt-jointed and bonded with an approved adhesive consistent with the application environment. Adhesive manufacturers' directions and procedures should be closely followed to ensure maximum bond strength. AquaDeck can be used on irregular surfaces and coverings.

RECOMMENDED WET AREA ADHESIVE

ACL Comcork recommend for all internal and external applications a two part epoxy resin adhesive should be used to ensure that correct bonding is achieved to the substrate. The adhesive manufacturers' specific instructions relative to the type of substrate being used must be complied with.

MAINTENANCE

AquaDeck is easily cleaned by hosing with water. No other surface treatment is required.

WARRANTY

ACL Comcork warrants AquaDeck floor covering, when installed correctly, to be free of defects in material and workmanship. ACL Comcork will replace, without charge for a period of twenty-four months after purchase, any AquaDeck floor covering found to be faulty due to defective material and/or workmanship. Failure or damage resulting from accident, abuse, misapplication, improper installation, consequential damage, normal wear and tear and colour fade are not covered by this warranty.



ACL Comcork

MANUFACTURED IN AUSTRALIA BY:
ACL COMCORK, Division of Automotive Components Limited, A.C.N. 006 542 785
7-15 Valley Street, GAKLEIGH SOUTH, VICTORIA 3167, AUSTRALIA
PH (03) 9544 2266 FAX (03) 9562 8883

AquaDeck - Proud to be Australian

AVAILABLE FROM: